

PLUMBERS CLASSIC® Model 2975PC

- Automatic submersible sump pump
- Maximum pumping capacity to 2580 gallons per hour
- Rugged thermoplastic body resists corrosion, impact, stress and heat
- Tethered float switch designed for minimum 12" diameter sump basin
- Heavy-duty 10 amp motor
- Easy installation, replaces pedestal or submersible sump pumps

1/2 HP
3 Year Warranty



Common Features

- Automatic submersible sump pump
- Durable, thermoplastic construction: completely corrosion-free
- Dependable motor and float switch for automatic or manual operation
- Designed for minimum 11" diameter sump basin
- 1-1/4" NPT discharge
- Easy installation, replaces pedestal or submersible sump pumps

MARK Model 2955

- Maximum pumping capacity to 1860 gallons per hour
- Powerful 10 amp motor with automatic thermal overload protection

1/3 HP
2 Year Warranty



Model 2955
Model 2905



MARK Model 2905

- Maximum pumping capacity to 1260 gallons per hour
- Durable 6 amp motor with automatic thermal overload protection

1/4 HP
1 Year Warranty



MARK Model 2957

- Automatic or manual submersible sump pump
- Durable, thermoplastic construction: completely corrosion-free
- Maximum pumping capacity to 1860 gallons per hour
- Powerful 10 amp motor with automatic thermal overload protection
- Automatic vertical switch designed for minimum 9" diameter sump basin

1/3 HP
2 Year Warranty



Performance

Model Number	HP	Warranty (Years)	Switch Type	Min. Sump Diameter	Float Switch		Gallons per Hour at Discharge Height Above Pumping Level					Max Lift No Flow
					On	Off	0	5	10	15	20	
2975PC	1/2	3	Float	12"	14"	7"	2580	2220	1800	900	300	23'
2955	1/3	2	Float	11"	11"	4"	1860	1740	1620	1260	720	28'
2905	1/4	1	Float	11"	11"	4"	1260	1140	1020	840	480	25'
2957	1/3	2	Vertical	9"	7"	2"	1860	1740	1620	1260	720	28'